



BIZOL Long Distance SAE 0W-30

Bizol Long Distance SAE 0W-30 is a highly modern, full synthetic, low-friction engine oil for the all-year use. The combination of unique synthetic base oils with an advanced additive technology results in an engine oil with low viscosity and high stability. It reliably prevents deposits, reduces friction losses in the engine, and protects from wear. It is suitable for use in petrol and diesel engines including turbo-charger and catalyst converters.

PROPERTIES

- High fuel savings
- Rapid oil supply at low temperatures
- Outstanding engine cleanliness
- Optimal oil pressure at all engine speeds
- Very high lubrication reliability and wear-protection
- Outstanding stability at high temperatures
- Suitable for catalytic converters and in turbo-chargers

PRICES

4 Litres \$57.50 Carton (4 x 4L) \$210

CLASSIFICATIONS, SPECIFICATIONS, APPROVALS, RECOMMENDATIONS:

ACEA A3/B4
API SL/CF
BMW Longlife-98
MB 229.3

VW 502.00/505.00

TECHNICAL DATA

Viscosity Class 0W-30 Density at 15°C, kg/m3 845 Viscosity at -35°C, mPa.s <6 200 Viscosity at 40°C, mm2/s 52 Viscosity at 100°C, mm2/s 10.1 Viscosity Index 186 Flash Point, °C 234 Pour Point, °C -45 Sulphated Ash, g/100g 1.1 TBN, mg KOH/g 9.5 ASTM Colour L4.5

FIELD OF APPLICATION

Recommended for modern cars with petrol and diesel engines with or without turbo-chargers and with or without charge air cooler. Especially suitable when there are long intervals between oil changes and high engine requirements to meet.

INSTRUCTIONS

Please follow the operating instructions of the vehicle and engine manufacturers.

PACKAGE SIZES

4 Litres