



Bizol ATF UniDrive

BIZOL ATF UniDrive is a full synthetic oil which belongs to the latest generation of automatic transmission fluids based on the synthesic technology combined with a modern, high-performance additive package. It meets the requirements of many car and automatic gear box manufacturers all over the world.

PROPERTIES

- ◆ Reliable under low temperatures
- ◆ Excellent protection against corrosion and wear
- ◆ Stable viscosity under high temperatures
- ◆ Outstanding anti-aging characteristics
- ◆ Good friction characteristics
- ◆ Multifunctional

PRICES

20 Litres

\$175

CLASSIFICATIONS, SPECIFICATIONS, APPROVALS, RECOMMENDATIONS:

Ford	Mercon V
Dexron	III H / VI
AE	LT71141
JASO	1-A
Allison	C4 / TES-295
Aisin AW	JWS 3309
Chrysler	ATF +3/+4
Subaru	ATF
Mitsubishi, Hyundai, Kia	SP-II / SP-III
Nissan	Matic D/J/K
Honda	Z-1
Mazda	ATF M-III / M-V
Toyota	T-II / T-IV
MAN	339 Typ Z, V1/Z1, V2/Z2
BMW	LA 2634, 7045 E, LT71141, 8072 B
Voith	H55.6336
ZF	TE-ML 02F, 03D, 04D, 05L, 09, 11A, 11B, 14A, 14B, 16L, 17C
MB	236.1, 236.2, 236.5, 236.6, 236.7, 236.9, 236.10, 236.11
Daimler	NAG-1
Volvo	97340, 97341
VW	G 055 025-A2, G 052 162-A1

TECHNICAL DATA

Density at 15°C, kg/m ³	850
Viscosity at -40°C, mPa/s	<20 000
Viscosity at 40°C, mm ² /s	34.4
Viscosity at 100°C, mm ² /s	7.3
Viscosity Index	185
Flash Point, °C	204
Pour Point, °C	-48
Colour	Red

FIELD OF APPLICATION	BIZOL ATF UniDrive can be used in automatic and mechanical gear boxes, in clutch and power steering systems as well as in hydraulic and auxiliary drive systems in both cars and commercial vehicles.
INSTRUCTIONS	Follow the operation instruction of the vehicle and engine manufacturers.
PACKAGE SIZES	20 Litres