



BIZOL Formula 1 SAE 0W-40

Bizol Formula 1 SAE 0W-40 is a highly modern, full synthetic, low-friction engine oil for year round use. The combination of unique synthetic base oils with an advanced additive technology results in an engine oil with low viscosity and high stability. It reliably prevents deposits, reduces friction losses in the engine, and protects from wear. Bizol Formula 1 SAE 0W-40 is recommended for use in petrol and diesel engines including turbo-chargers and catalyst converters.

PROPERTIES

- ◆ Excellent fuel economy
- ◆ Rapid oil supply at low temperatures
- ◆ Optimal oil pressure at all engine speeds
- ◆ Very high lubrication reliability and wear-protection
- ◆ Outstanding engine cleanliness
- ◆ Outstanding stability at high temperature
- ◆ Extremely low evaporation loss
- ◆ Suitable for catalytic converters and in turbo-chargers

PRICES

4 Litres	\$55
Carton (4 x 4L)	\$200
20 Litres	\$175

CLASSIFICATIONS, SPECIFICATIONS, APPROVALS, RECOMMENDATIONS:

ACEA	A3/B4
API	SM/CF
BMW	Longlife-98
MB	229.3
Opel/Saab	GM-LL-B-025
VW	502.00/505.00
Porsche	A40

TECHNICAL DATA

Viscosity Class	0W-40
Density at 15°C, kg/m ³	850
Viscosity at -35°C, mPa.s	<6 200
Viscosity at 40°C, mm ² /s	80
Viscosity at 100°C, mm ² /s	14.0
Viscosity Index	181
Flash Point, °C	230
Pour Point, °C	-39
Sulphated Ash, g/100g	1.2
TBN, mg KOH/g	9.6
ASTM Colour	L4.0

FIELD OF APPLICATION

Recommended for modern cars with petrol and diesel engines with or without turbo-chargers and with or without intercooler. Especially suitable when there are long intervals between oil changes and high engine requirements to meet.

INSTRUCTIONS

Please follow the operating instructions of the vehicle and engine manufacturers.

PACKAGE SIZES

4 Litres, 20 Litres