



Bizol CVT Drive

BIZOL CVT Drive is a full synthetic high-performance automatic transmission fluid developed specially for the latest generation of CVT gear boxes. Selected base oils and a well adjusted additive package protect against foam formation, which is very important in CVT gear boxes. This product has excellent anti-aging and anti-oxidation characteristics.

PROPERTIES

- High shear stability
- ♦ Excellent protection against foam formation
- Very good anti-aging and anti-oxidation characteristics
- Reliable lubrication even under low temperatures
- ♦ Advanced protection against wear and corrosion

PRICES 20 Litres \$250

CLASSIFICATIONS, SPECIFICATIONS, APPROVALS, RECOMMENDATIONS:

MB 236.20 VW TL 52180

Ford CVT30, Mercon C, CVT23

Toyota TC
Hyundai, Kia, Mitsubishi SP-III
Mitsubishi CVTF-J1
Nissan NS-2
Honda HMMF

Subaru NS-2, Lineartronic CVTF Suzuki TC, NS-2, CVT Green 1

GM Satur

DEX-CVT

Dodge - Jeep CVTF+4 Mini Cooper EZI 7/99

NOT SUITABLE FOR HYBRID CVT

TECHNICAL DATA Density at 15°C, kg/m3

Viscosity at -40°C, mPa.s <12 000
Viscosity at 40°C, mm2/s 34
Viscosity at 100°C, mm2/s 7
Viscosity Index 173
Flash Point, °C 210
Pour Point, °C -52
Colour Yellowish

FIELD OF APPLICATION

BIZOL CVT Drive was approved for use in Autotronic gear boxes installed at Mercedes A and B classes. It is also applicable to many variable automatic transmissions of different manufacturers, among others to Audi Multitronic.

848

INSTRUCTIONS

Follow the operation instruction of the vehicle and engine manufacturers.

PACKAGE SIZES

20 Litres