



BIZOL Platin SAE 5W-40

Bizol Platin SAE 5W-40 is a full synthetic, high-performance, low-friction engine oil designed for all-year use in modern engines. It reduces oil and fuel consumption and grants an optimal lubrication even under extreme conditions. It shows an immediate lubricating effect at cold start due to its constant wide-range viscosity, which resists even extreme temperature fluctuations. It grants the optimal engine performance and oil pressure at all revolutions per minute. The improved wear-protection prolongs the service life of the engine.

PROPERTIES

- ◆ Long service life of the engine due to very high level of wear-protection
- ◆ Miscible and compatible with commercially available engine oils.
- ◆ Rapid oil supply at low temperatures
- ◆ Very high resistance to shearing strain and ageing
- ◆ Outstanding engine cleanliness
- ◆ Smooth engine running
- ◆ Suitable for catalytic converters and in turbochargers
- ◆ Extremely low evaporation loss

PRICES

| | |
|------------------------|----------------|
| 5 Litres | \$59.50 |
| Carton (4 x 5L) | \$218 |
| 20 Litres | \$170 |

CLASSIFICATIONS, SPECIFICATIONS, APPROVALS, RECOMMENDATIONS:

| | |
|-----------|---------------|
| ACEA | A3/B4 |
| API | SM/CF |
| BMW | Longlife-98 |
| MB | 229.3 |
| Opel/Saab | GM-LL-B-025 |
| VW | 502.00/505.00 |
| Porsche | A40 |
| Fiat | 9.55535 H2/M2 |

TECHNICAL DATA

| | |
|--|-------|
| Viscosity Class | 5W-40 |
| Density at 15°C, kg/m ³ | 850 |
| Viscosity at 40°C, mm ² /s | 86 |
| Viscosity at 100°C, mm ² /s | 14.1 |
| Viscosity Index | 170 |
| Flash Point, °C | 230 |
| Pour Point, °C | -36 |
| Sulphated Ash, g/100g | 1.2 |
| TBN, mg KOH/g | 9.6 |
| ASTM Colour | L3.5 |

FIELD OF APPLICATION

An all-year oil for modern petrol engines with multi-valve technology and for turbo-chargers. Especially suitable when there are long intervals between oil changes and high engine requirements to meet.

INSTRUCTIONS

Please follow the operating instructions of the vehicle and engine manufacturers.

PACKAGE SIZES

5 Litres, 20 Litres