



## Product Data Sheet

# Masterlube 30 SAE 30

### Product Description

**Masterlube 30** is a low ash, heavy duty diesel engine oil formulated to lubricate engines operating under severe stress conditions. The low phosphorous and low sulphated ash content ensures its use for mixed fleet operations, including those with petrol engines with catalytic converters.

### Specifications and Approvals

**Masterlube 30** meets or exceeds the following specifications:

- API CF-4/CF-2/CF, SJ/SH/SG
- MAN 270
- MB 227.0
- US MIL-L-46152C, 2104D

### Applications and Benefits

**Masterlube 30** is suited for use in turbocharged or naturally aspirated Diesel, Petrol (leaded and unleaded fuel), as well as LPG engines. Designed for cars, light commercials, trucks, earthmoving equipment, stationary engines and off-highway where a 30 weight oil is specified.

### Package Information

**200 Litres, 20 Litres.**

**The Oilman Group Pty Ltd**  
[www.oilman.com.au](http://www.oilman.com.au)

Head Office: (08) 8262 9399  
Adelaide: (08) 8349 9277  
Brisbane: (07) 3216 7196  
Darwin: 1300 133 783  
Melbourne: 1300 133 783  
Perth: 1300 133 783

### Typical Characteristics

Density at 15°C	0.878
Kinematic Viscosity at 40°C, mm <sup>2</sup> /s (cSt)	110
Kinematic Viscosity at 100°C, mm <sup>2</sup> /s (cSt)	12
Viscosity Index	99
Sulphated Ash, wt%	1
TBN, mgKOH/g	8.2
Pour Point °C	-24
Flash Point °C	230

Typical Characteristics are average values, and may vary due to normal manufacturing tolerances. The information contained herein is subject to change without notice.