



Product Data Sheet

Masterlube 300 20w/50 CH-4/SJ

Product Description

Masterlube 300 is a versatile and economical high performance diesel engine oil meeting API CH-4/SJ standards in diesel/petrol lubrication. It has been specifically formulated as a stay in grade oil to equally perform in engines running on diesel, petrol or LPG, whether turbocharged, or naturally aspirated.

Specifications and Approvals

Masterlube 300 meets or exceeds the following specifications:

- API CH-4/SJ
- CCMC D4/G4/PD-2
- US MIL-L-46152D

Applications and Benefits

Masterlube 300 is recommended for use in European, Japanese and pre-1998 US turbocharged and non-turbocharged diesel engines.

It is also suitable for automotive petrol engines and 4 wheel drives due to the high level of detergents and dispersants that provide excellent protection from typical city stop-start operation that promotes acid sludge formation in the engine.

Package Information

200 Litres, 20 Litres.

Typical Characteristics

Density at 15°C	0.886
Kinematic Viscosity at 40°C, mm ² /s (cSt)	140
Kinematic Viscosity at 100°C, mm ² /s (cSt)	17.2
Viscosity Index	129
Sulphated Ash, wt%	1.15
TBN, mgKOH/g	8.9
Pour Point °C	-22
Flash Point °C	225

The Oilman Group Pty Ltd
www.oilman.com.au

Head Office: (08) 8262 9399
Adelaide: (08) 8349 9277
Brisbane: (07) 3216 7196
Darwin: 1300 133 783
Melbourne: 1300 133 783
Perth: 1300 133 783

Typical Characteristics are average values, and may vary due to normal manufacturing tolerances. The information contained herein is subject to change without notice.